

WHEELS

Product group	Wheels
Item number	59913303
Valid wheel size	500 / 45 R 20
Brand	Alliance
Tread pattern	381
Valid rim size	16 x 20
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	4125
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15216080
LI / SI / PR	145 A8 / 157 A8
Load capacity 1 [kg]	2900
Speed 1 [km/h].	40
Load capacity 2 [kg]	4125
Speed 2 [km/h].	40
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	108,01
ECE regulation number	ECE 106

Section width (mm)	502
Stat. radius (SLR) [mm]	412
Rolling circumference [mm].	2877
Tread depth (mm)	14,5
E-Ready	No
Assembly Item no. Rim	• 31610601
Load capacity of rim 1 [kg]	5000
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	4,00
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve

Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade