

WHEELS

Product group	Wheels
Item number	59913304
Valid wheel size	500 / 45 R 20
Brand	Alliance
Tread pattern	381
Valid rim size	16 x 20
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	4125
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15216080
LI / SI / PR	145 A8 / 157 A8
Load capacity 1 [kg]	2900
Speed 1 [km/h].	40
Load capacity 2 [kg]	4125
Speed 2 [km/h].	40
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	108,01
ECE regulation number	ECE 106

Section width (mm)	502
Stat. radius (SLR) [mm]	412
Rolling circumference [mm].	2877
Tread depth (mm)	14,5
E-Ready	No
Assembly Item no. Rim	• 33060174
Load capacity of rim 1 [kg]	5350
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	4500
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	4,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161

Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade