

## WHEELS

|                                   |                     |
|-----------------------------------|---------------------|
| Product group                     | Wheels              |
| Item number                       | 59913315            |
| Valid wheel size                  | 500 / 45 - 22.5     |
| Brand                             | Alliance            |
| Tread pattern                     | Flotation 328       |
| Valid rim size                    | AG 16.00 x 22.5 TH2 |
| Rim connection                    | 8/221/275           |
| Bolt hole design                  | A2                  |
| Rim colour                        | Silver              |
| Load capacity complete wheel [kg] | 3750                |
| Speed complete wheel [km/h]       | 40                  |



## Technical Informations

|                            |                        |
|----------------------------|------------------------|
| Assembly Item no. Tyres    | • 15212575             |
| LI / SI / PR               | 142 A8 / 154 A8, 16 PR |
| Load capacity 1 [kg]       | 2650                   |
| Speed 1 [km/h].            | 40                     |
| Load capacity 2 [kg]       | 3750                   |
| Speed 2 [km/h].            | 40                     |
| Antistatic                 | No                     |
| Tyre colour                | Black                  |
| Nettogewicht [kg] (gültig) | 126,42                 |
| ECE regulation number      | ECE 106                |
| Section width (mm)         | 500                    |

|                                |                               |
|--------------------------------|-------------------------------|
| Stat. radius (SLR) [mm]        | 455                           |
| Rolling circumference [mm].    | 3153                          |
| Tread depth (mm)               | 25,0                          |
| E-Ready                        | No                            |
| Assembly Item no. Rim          | • 30812624                    |
| Load capacity of rim 1 [kg]    | 7250                          |
| Speed Rims 1 [km/h]            | 40                            |
| Load capacity of rim 2 [kg]    | 5300                          |
| Speed Rims 2 [km/h]            | 65                            |
| Maximum speed [km/h].          | 50                            |
| Maximum air pressure [bar].    | 3,60                          |
| Type of drive                  | Angetriebene & gezogene Achse |
| Hump                           | TH2                           |
| Valve protection               | VS H                          |
| Single / multi-part            | einteilig                     |
| Rim material                   | steel                         |
| RAL                            | RAL9006                       |
| Cavity Sealed                  | No                            |
| Ventilation holes              | No                            |
| Verschweißung beidseitig       | No                            |
| Rim centering                  | BC                            |
| Number of bolt holes           | 8                             |
| Bolt hole diameter [mm]        | 21.5                          |
| Countersinking                 | Sphere                        |
| Spherical countersink [mm].    | R16                           |
| hub hole diameter [mm].        | 221                           |
| Bolt hole circle diameter [mm] | 275                           |

---

|                          |                |
|--------------------------|----------------|
| Valve seat               | External Valve |
| Valve hole diameter [mm] | 15.7           |
| Preassembled valve       | No             |
| Valve design             | Metal valve    |
| Valve designation ETRTO  | V3.20.1        |
| Valve length [mm]        | 41.0           |
| Valve angle [°]          | gerade         |