

WHEELS

Product group	Wheels
Item number	59913326
Valid wheel size	500 / 45 - 22.5
Brand	Alliance
Tread pattern	Flotation 328
Valid rim size	AG 16.00 x 22.5 H2
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	3750
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15212575
LI / SI / PR	142 A8 / 154 A8, 16 PR
Load capacity 1 [kg]	2650
Speed 1 [km/h].	40
Load capacity 2 [kg]	3750
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	123,42
ECE regulation number	ECE 106
Section width (mm)	500

Stat. radius (SLR) [mm]	455
Rolling circumference [mm].	3153
Tread depth (mm)	25,0
E-Ready	No
Assembly Item no. Rim	• 33060361
Load capacity of rim 1 [kg]	7250
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5300
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,60
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281

Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V3.20.1
Valve length [mm]	41.0
Valve angle [°]	gerade