

WHEELS

Product group	Wheels
Item number	59913327
Valid wheel size	500 / 60 - 22.5
Brand	Alliance
Tread pattern	Flotation 331
Valid rim size	AG 16.00 x 22.5 H2
Rim connection	8/221/275
Bolt hole design	A3
Offset (mm)	+10
Rim colour	Silver
Load capacity complete wheel [kg]	4875
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15212582
LI / SI / PR	151 A8 / 163 A8, 16 PR
Load capacity 1 [kg]	3450
Speed 1 [km/h].	40
Load capacity 2 [kg]	4875
Speed 2 [km/h].	40
Direction	Right
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	130,15
ECE regulation number	ECE 106

Section width (mm)	503
Stat. radius (SLR) [mm]	519
Rolling circumference [mm].	3472
Tread depth (mm)	39,0
E-Ready	No
Assembly Item no. Rim	• 33060367
Load capacity of rim 1 [kg]	6800
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5000
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,20
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18

hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade