

WHEELS

Product group	Wheels
Item number	59913367
Valid wheel size	500 / 60 - 22.5
Brand	Alliance
Tread pattern	Flotation 328
Valid rim size	AG 16.00 x 22.5 H2
Rim connection	8/221/275
Bolt hole design	A2
Offset (mm)	-50
Rim colour	Silver
Rim series	Profiline+
Load capacity complete wheel [kg]	5150
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15212584
LI / SI / PR	153 A8 / 165 A8, 18 PR
Load capacity 1 [kg]	3650
Speed 1 [km/h].	40
Load capacity 2 [kg]	5150
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	132,15
ECE regulation number	ECE 106

Section width (mm)	500
Stat. radius (SLR) [mm]	510
Rolling circumference [mm].	3470
Tread depth (mm)	26,0
E-Ready	No
Assembly Item no. Rim	• 31612676
Load capacity of rim 1 [kg]	7010
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5150
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,60
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	221

Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade