

## WHEELS

Product group	Wheels
Item number	59913437
Valid wheel size	600 / 40 - 22.5
Brand	Alliance
Tread pattern	Flotation 331
Valid rim size	AG 20.00 x 22.5 TH2
Rim connection	10/281/335
Bolt hole design	B3
Rim colour	Grey
Load capacity complete wheel [kg]	6500
Speed complete wheel [km/h]	30
Nettogewicht [kg] (gültig)	165,43
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15212643
LI / SI / PR	173 A6 / 169 A8, 18 PR
Load capacity 1 [kg]	6500
Speed 1 [km/h].	30
Load capacity 2 [kg]	5800
Speed 2 [km/h].	40
Maximum air pressure [bar].	6,00
TL/TT	TL
Tyre colour	Black

E-Ready	No
Carcass properties	HD
Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	600
Stat. radius (SLR) [mm]	505
Rolling circumference [mm].	3280
Tread depth (mm)	39,0
Assembly Item no. Rim	• 39122846
Load capacity of rim 1 [kg]	7736
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	10
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Bolt hole design EUWA	B22 DS 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC
Rim material	steel
RAL	RAL7024
Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig
Hump	TH2

---

Valve protection	VSH
Surface treatment	SB
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade