

## WHEELS

Product group	Wheels
Item number	59913437
Valid wheel size	600 / 40 - 22.5
Brand	Alliance
Tread pattern	Flotation 331
Valid rim size	AG 20.00 x 22.5 TH2
Rim connection	10/281/335
Bolt hole design	B3
Rim colour	Grey
Load capacity complete wheel [kg]	6500
Speed complete wheel [km/h]	30



## Technical Informations

Assembly Item no. Tyres	• 15212643
LI / SI / PR	173 A6 / 169 A8, 18 PR
Load capacity 1 [kg]	6500
Speed 1 [km/h].	30
Load capacity 2 [kg]	5800
Speed 2 [km/h].	40
Carcass properties	HD
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	165,43
ECE regulation number	ECE 106

Section width (mm)	600
Stat. radius (SLR) [mm]	505
Rolling circumference [mm].	3280
Tread depth (mm)	39,0
E-Ready	No
Assembly Item no. Rim	• 39122846
Load capacity of rim 1 [kg]	7736
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	6,00
Type of drive	Angetriebene & gezogene Achse
Hump	TH2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
Surface treatment	SB
RAL	RAL7024
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281

---

<b>Bolt hole circle diameter [mm]</b>	335
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No
<b>Valve design</b>	Metal valve
<b>Valve designation ETRTO</b>	V5.01.1
<b>Valve length [mm]</b>	50.0
<b>Valve angle [°]</b>	gerade