

## WHEELS

Product group	Wheels
Item number	59913462
Valid wheel size	710 / 40 - 22.5
Brand	Nokian
Tread pattern	Nordman Forest TRS L-2
Valid rim size	AG 24.00 x 22.5 H2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-85
Rim colour	Yellow
Load capacity complete wheel [kg]	4250
Speed complete wheel [km/h]	10



## Technical Informations

Assembly Item no. Tyres	• 17415027
LI / SI / PR	158 A2 / 151 A8, 16 PR
Load capacity 1 [kg]	4250
Speed 1 [km/h].	10
Load capacity 2 [kg]	3450
Speed 2 [km/h].	40
TRA Code	LS-2
Carcass properties	SF
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	228,94

ECE regulation number	not necessary
Section width (mm)	710
Stat. radius (SLR) [mm]	539
Dynamic radius [mm]	563
Rolling circumference [mm].	3537
E-Ready	No
Assembly Item no. Rim	• 33060449
Load capacity of rim 1 [kg]	8000
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	10250
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,20
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Valve protection	VS V
Single / multi-part	einteilig
Rim material	steel
RAL	RAL1004
Cavity Sealed	No
Forest reinforcement	flange reinforcement Ø16 mm
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36

---

<b>Bolt hole diameter [mm]</b>	27
<b>Countersinking</b>	Sphere
<b>Spherical countersink [mm].</b>	R18
<b>hub hole diameter [mm].</b>	281
<b>Bolt hole circle diameter [mm]</b>	335
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No