

WHEELS

Product group	Wheels
Item number	59913517
Valid wheel size	600 / 50 - 22.5
Brand	Alliance
Tread pattern	Flotation 328
Valid rim size	AG 20.00 x 22.5 TH2
Rim connection	8/221/275
Bolt hole design	A3
Offset (mm)	-50
Rim colour	Silver
Rim series	Profiline
Load capacity complete wheel [kg]	4125
Speed complete wheel [km/h]	65



Technical Informations

Assembly Item no. Tyres	• 15212638
LI / SI / PR	158 D / 157 E, 16 PR
Load capacity 1 [kg]	4250
Speed 1 [km/h].	65
Load capacity 2 [kg]	4125
Speed 2 [km/h].	70
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	159,14

ECE regulation number	ECE 106
Section width (mm)	600
Stat. radius (SLR) [mm]	520
Rolling circumference [mm].	3450
Tread depth (mm)	25,0
E-Ready	No
Assembly Item no. Rim	• 32012687
Load capacity of rim 1 [kg]	7070
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5310
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	2,60
Type of drive	Towed axle
Hump	TH2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere

Spherical countersink [mm].	R18
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade