

WHEELS

Product group	Wheels
Item number	59913530
Valid wheel size	600 / 50 R 22.5
Brand	Alliance
Tread pattern	390
Valid rim size	AG 20.00 x 22.5 TH2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-50
Rim colour	Silver
Rim series	Profiline
Load capacity complete wheel [kg]	4375
Speed complete wheel [km/h]	70



Technical Informations

Assembly Item no. Tyres	• 15215570
LI / SI / PR	162 D / 159 E
Load capacity 1 [kg]	4750
Speed 1 [km/h].	65
Load capacity 2 [kg]	4375
Speed 2 [km/h].	70
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	187,90

ECE regulation number	ECE 106
Section width (mm)	583
Stat. radius (SLR) [mm]	531
Rolling circumference [mm].	3605
Tread depth (mm)	24,5
E-Ready	No
Assembly Item no. Rim	• 32012686
Load capacity of rim 1 [kg]	7070
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5310
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	70
Maximum air pressure [bar].	4,00
Type of drive	Angetriebene & gezogene Achse
Hump	TH2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere

Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade