

WHEELS

Product group	Wheels
Item number	59913531
Valid wheel size	600 / 50 R 22.5
Brand	Alliance
Tread pattern	390
Valid rim size	AG 20.00 x 22.5 TH2
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+60
Rim colour	Silver
Load capacity complete wheel [kg]	5300
Speed complete wheel [km/h]	80



Technical Informations

Assembly Item no. Tyres	• 15215566
LI / SI / PR	166 F
Load capacity 1 [kg]	5300
Speed 1 [km/h].	80
Carcass properties	All-Steel
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	209,81
ECE regulation number	ECE 54
Section width (mm)	585
Stat. radius (SLR) [mm]	539

Rolling circumference [mm].	3510
Tread depth (mm)	25,0
E-Ready	No
Assembly Item no. Rim	• 39122847
Load capacity of rim 1 [kg]	7070
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5450
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	80
Maximum air pressure [bar].	6,00
Type of drive	Angetriebene & gezogene Achse
Hump	TH2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335

Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade