

## WHEELS

Product group	Wheels
Item number	59913535
Valid wheel size	600 / 50 R 22.5
Brand	Alliance
Tread pattern	382
Valid rim size	AG 20.00 x 22.5 H2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-50
Rim colour	Silver
Rim series	Profiline
Load capacity complete wheel [kg]	5000
Speed complete wheel [km/h]	100



## Technical Informations

Assembly Item no. Tyres	• 15215572
LI / SI / PR	164 J
Load capacity 1 [kg]	5000
Speed 1 [km/h].	100
Carcass properties	All-Steel
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	194,80
ECE regulation number	ECE 54
Section width (mm)	600

Stat. radius (SLR) [mm]	535
Rolling circumference [mm].	3587
Tread depth (mm)	25,0
E-Ready	No
Assembly Item no. Rim	• 31612685
Load capacity of rim 1 [kg]	5000
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	6,50
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Number of additional holes	10
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335

---

Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade