

## WHEELS

Product group	Wheels
Item number	59913538
Valid wheel size	600 / 50 R 22.5
Brand	Alliance
Tread pattern	398
Valid rim size	AG 20.00 x 22.5 H2
Rim connection	10/281/335
Bolt hole design	M22
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	5000
Speed complete wheel [km/h]	100



## Technical Informations

Assembly Item no. Tyres	• 15216303
LI / SI / PR	164 J
Load capacity 1 [kg]	5000
Speed 1 [km/h].	100
Carcass properties	All-Steel POR
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	206.23
ECE regulation number	ECE 54
Section width (mm)	620
Stat. radius (SLR) [mm]	541

Rolling circumference [mm].	3605
Tread depth (mm)	30,0
E-Ready	No
Assembly Item no. Rim	• 33060412
Load capacity of rim 1 [kg]	5100
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	6,50
Number of bolt holes	10
Bolt hole design EUWA	M22
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	26
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Single / multi-part	einteilig
Rim centering	HB
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Preassembled valve	No
TPMS-kompatibles Ventil	No