

WHEELS

Product group	Wheels
Item number	59913541
Valid wheel size	600 / 50 R 22.5
Brand	Alliance
Tread pattern	398
Valid rim size	AG 20.00 x 22.5 H2
Rim connection	10/281/335
Bolt hole design	M22
Rim colour	Silver
Load capacity complete wheel [kg]	5000
Speed complete wheel [km/h]	100



Technical Informations

Assembly Item no. Tyres	• 15216303
LI / SI / PR	164 J
Load capacity 1 [kg]	5000
Speed 1 [km/h].	100
Carcass properties	All-Steel POR
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	206,23
ECE regulation number	ECE 54
Section width (mm)	620
Stat. radius (SLR) [mm]	541

Rolling circumference [mm].	3605
Tread depth (mm)	30,0
E-Ready	No
Assembly Item no. Rim	• 33060411
Load capacity of rim 1 [kg]	5100
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	100
Maximum air pressure [bar].	6,50
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	HB
Number of bolt holes	10
Bolt hole design EUWA	M22
Bolt hole diameter [mm]	26
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No