

## WHEELS

|                                   |                    |
|-----------------------------------|--------------------|
| Product group                     | Wheels             |
| Item number                       | 59913709           |
| Valid wheel size                  | 560 / 45 R 22.5    |
| Brand                             | BKT                |
| Tread pattern                     | Ridemax FL 693 M   |
| Valid rim size                    | AG 16.00 x 22.5 H2 |
| Rim connection                    | 10/281/335         |
| Bolt hole design                  | A3                 |
| Rim colour                        | Silver             |
| Load capacity complete wheel [kg] | 3550               |
| Speed complete wheel [km/h]       | 65                 |
| Nettogewicht [kg] (gültig)        | 147,05             |
| RDRA (Reifendruckregelanlage)     | No                 |
| RDKS (Reifendruckkontrollsystem)  | No                 |



## Technical Informations

|                             |              |
|-----------------------------|--------------|
| Assembly Item no. Tyres     | • 15715116   |
| LI / SI / PR                | 152 D        |
| Load capacity 1 [kg]        | 3550         |
| Speed 1 [km/h].             | 65           |
| Maximum air pressure [bar]. | 4,00         |
| TL/TT                       | TL           |
| Tyre colour                 | Black        |
| E-Ready                     | No           |
| Carcass properties          | Steel Belted |

|                                |                               |
|--------------------------------|-------------------------------|
| Antistatic                     | No                            |
| ECE regulation number          | ECE 106                       |
| Section width (mm)             | 543                           |
| Stat. radius (SLR) [mm]        | 457                           |
| Rolling circumference [mm].    | 3306                          |
| Tread depth (mm)               | 21,0                          |
| Tyre capacity 75% [ltr.]       | 185                           |
| Assembly Item no. Rim          | • 33060354                    |
| Load capacity of rim 1 [kg]    | 7600                          |
| Speed Rims 1 [km/h]            | 40                            |
| Load capacity of rim 2 [kg]    | 5600                          |
| Speed Rims 2 [km/h]            | 65                            |
| Maximum speed [km/h].          | 70                            |
| Type of drive                  | Angetriebene & gezogene Achse |
| Number of bolt holes           | 10                            |
| hub hole diameter [mm].        | 281                           |
| Bolt hole circle diameter [mm] | 335                           |
| Bolt hole diameter [mm]        | 27                            |
| Bolt hole design EUWA          | B22 ES 36                     |
| Countersinking                 | Sphere                        |
| Spherical countersink [mm].    | R18                           |
| Rim centering                  | BC                            |
| Rim material                   | steel                         |
| RAL                            | RAL9006                       |
| Valve seat                     | External Valve                |
| Ventilation holes              | No                            |
| Single / multi-part            | einteilig                     |

---

|                          |             |
|--------------------------|-------------|
| Hump                     | H2          |
| Valve protection         | VSH         |
| Cavity Sealed            | No          |
| Verschweißung beidseitig | No          |
| Assembly Item no. Valve  | • 47201038  |
| Preassembled valve       | No          |
| TPMS-kompatibles Ventil  | No          |
| Valve hole diameter [mm] | 15.7        |
| Valve design             | Metal valve |
| Valve designation ETRTO  | V5.01.1     |
| Valve length [mm]        | 50.0        |
| Valve angle [°]          | gerade      |