

WHEELS

Product group	Wheels
Item number	59913736
Valid wheel size	580 / 65 R 22.5
Brand	BKT
Tread pattern	Ridemax FL 693 M
Valid rim size	AG 16.00 x 22.5 H2
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	5300
Speed complete wheel [km/h]	65



Technical Informations

Assembly Item no. Tyres	• 15715128
LI / SI / PR	166 D / 163 E
Load capacity 1 [kg]	5300
Speed 1 [km/h].	65
Load capacity 2 [kg]	4875
Speed 2 [km/h].	70
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	175,37
ECE regulation number	ECE 106

Section width (mm)	577
Stat. radius (SLR) [mm]	572
Rolling circumference [mm].	4031
Tread depth (mm)	21,0
Tyre capacity 75% [ltr.]	512
E-Ready	No
Assembly Item no. Rim	• 33060361
Load capacity of rim 1 [kg]	7250
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5300
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	4,00
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere

Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade