

## WHEELS

Product group	Wheels
Item number	59913831
Valid wheel size	16.5 / 85 - 28
Brand	Alliance
Tread pattern	324
Valid rim size	DW 15 L x 28
Rim connection	10/176/225
Bolt hole design	A3
Offset (mm)	+80
Rim colour	Silver
Load capacity complete wheel [kg]	4375
Speed complete wheel [km/h]	40



## Technical Informations

Assembly Item no. Tyres	• 15222490
LI / SI / PR	163 A6 / 159 A8, 12 PR
Load capacity 1 [kg]	4875
Speed 1 [km/h].	30
Load capacity 2 [kg]	4375
Speed 2 [km/h].	40
Carcass properties	HD
Direction	Right
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	157,94

ECE regulation number	ECE 106
Section width (mm)	417
Stat. radius (SLR) [mm]	626
Rolling circumference [mm].	4130
Tread depth (mm)	31,0
Number of lugs	20x2
E-Ready	No
Assembly Item no. Rim	• 39123022
Load capacity of rim 1 [kg]	13715
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	12069
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	2,80
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Knurling	with knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27

---

Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	176
Bolt hole circle diameter [mm]	225
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No