

WHEELS

Product group	Wheels
Item number	59913842
Valid wheel size	750 / 60 R 30.5
Brand	BKT
Tread pattern	Ridemax FL 693 M
Valid rim size	AG 24.00 x 30.5 TH2
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Silver
Rim series	Profiline
Load capacity complete wheel [kg]	8250
Speed complete wheel [km/h]	65



Technical Informations

Assembly Item no. Tyres	• 15715250
LI / SI / PR	181 D
Load capacity 1 [kg]	8250
Speed 1 [km/h].	65
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	377,44
ECE regulation number	ECE 106
Section width (mm)	754
Stat. radius (SLR) [mm]	728

Rolling circumference [mm].	5092
Tread depth (mm)	26,0
Tyre capacity 75% [ltr.]	981
E-Ready	No
Assembly Item no. Rim	• 32013120
Load capacity of rim 1 [kg]	11220
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	8250
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	4,00
Type of drive	Angetriebene & gezogene Achse
Hump	TH2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281

Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade