

## WHEELS

|                                   |                     |
|-----------------------------------|---------------------|
| Product group                     | Wheels              |
| Item number                       | 59913843            |
| Valid wheel size                  | 750 / 60 R 30.5     |
| Brand                             | BKT                 |
| Tread pattern                     | Ridemax FL 693 M    |
| Valid rim size                    | AG 24.00 x 30.5 TH2 |
| Rim connection                    | 10/281/335          |
| Bolt hole design                  | A3                  |
| Offset (mm)                       | -50                 |
| Rim colour                        | Silver              |
| Rim series                        | Profiline           |
| Load capacity complete wheel [kg] | 8250                |
| Speed complete wheel [km/h]       | 65                  |
| Nettogewicht [kg] (gültig)        | 377,44              |
| RDRA (Reifendruckregelanlage)     | No                  |
| RDKS (Reifendruckkontrollsystem)  | No                  |



## Technical Informations

|                             |            |
|-----------------------------|------------|
| Assembly Item no. Tyres     | • 15715250 |
| LI / SI / PR                | 181 D      |
| Load capacity 1 [kg]        | 8250       |
| Speed 1 [km/h].             | 65         |
| Maximum air pressure [bar]. | 4,00       |
| TL/TT                       | TL         |
| Tyre colour                 | Black      |

|                                |                               |
|--------------------------------|-------------------------------|
| E-Ready                        | No                            |
| Carcass properties             | Steel Belted                  |
| Antistatic                     | No                            |
| ECE regulation number          | ECE 106                       |
| Section width (mm)             | 754                           |
| Stat. radius (SLR) [mm]        | 728                           |
| Rolling circumference [mm].    | 5092                          |
| Tread depth (mm)               | 26,0                          |
| Tyre capacity 75% [ltr.]       | 736                           |
| Assembly Item no. Rim          | • 32013121                    |
| Load capacity of rim 1 [kg]    | 11220                         |
| Speed Rims 1 [km/h]            | 40                            |
| Load capacity of rim 2 [kg]    | 8250                          |
| Speed Rims 2 [km/h]            | 65                            |
| Maximum speed [km/h].          | 65                            |
| Type of drive                  | Angetriebene & gezogene Achse |
| Number of bolt holes           | 10                            |
| hub hole diameter [mm].        | 281                           |
| Bolt hole circle diameter [mm] | 335                           |
| Bolt hole diameter [mm]        | 27                            |
| Bolt hole design EUWA          | B22 ES 36                     |
| Countersinking                 | Sphere                        |
| Spherical countersink [mm].    | R18                           |
| Rim centering                  | BC                            |
| Rim material                   | steel                         |
| RAL                            | RAL9006                       |
| Valve seat                     | External Valve                |

---

|                          |                  |
|--------------------------|------------------|
| Ventilation holes        | No               |
| Single / multi-part      | einteilig        |
| Hump                     | TH2              |
| Cavity Sealed            | No               |
| Knurling                 | without knurling |
| Verschweißung beidseitig | No               |
| Assembly Item no. Valve  | • 47201039       |
| Preassembled valve       | No               |
| TPMS-kompatibles Ventil  | No               |
| Valve hole diameter [mm] | 15.7             |
| Valve design             | Rubber valve     |
| Valve length [mm]        | 55.0             |
| Valve angle [°]          | gerade           |