

## WHEELS

Product group	Wheels
Item number	59913858
Valid wheel size	850 / 50 R 30.5
Brand	Alliance
Tread pattern	390
Valid rim size	AG 28.00 x 30.5 TH2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-100
Rim colour	Silver
Rim series	Profiline
Load capacity complete wheel [kg]	8500
Speed complete wheel [km/h]	65



## Technical Informations

Assembly Item no. Tyres	• 15215810
LI / SI / PR	182 D
Load capacity 1 [kg]	8500
Speed 1 [km/h].	65
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	409,45
ECE regulation number	ECE 106
Section width (mm)	882

Stat. radius (SLR) [mm]	742
Rolling circumference [mm].	4860
Tread depth (mm)	27,0
E-Ready	No
Assembly Item no. Rim	• 32013422
Load capacity of rim 1 [kg]	11560
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	8500
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	4,00
Type of drive	Angetriebene & gezogene Achse
Hump	TH2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335

---

Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade