

WHEELS

| | |
|-----------------------------------|---------------------|
| Product group | Wheels |
| Item number | 59913862 |
| Valid wheel size | 750 / 60 R 30.5 |
| Brand | Alliance |
| Tread pattern | 390 |
| Valid rim size | AG 24.00 x 30.5 TH2 |
| Rim connection | 10/281/335 |
| Bolt hole design | A3 |
| Offset (mm) | -50 |
| Rim colour | Silver |
| Rim series | Profiline |
| Load capacity complete wheel [kg] | 8250 |
| Speed complete wheel [km/h] | 65 |
| Nettogewicht [kg] (gültig) | 388,27 |
| RDRA (Reifendruckregelanlage) | No |
| RDKS (Reifendruckkontrollsystem) | No |



Technical Informations

| | |
|-----------------------------|------------|
| Assembly Item no. Tyres | • 15215800 |
| LI / SI / PR | 181 D |
| Load capacity 1 [kg] | 8250 |
| Speed 1 [km/h]. | 65 |
| Maximum air pressure [bar]. | 4,00 |
| TL/TT | TL |
| Tyre colour | Black |

| | |
|--------------------------------|-------------------------------|
| E-Ready | No |
| Carcass properties | Steel Belted |
| Antistatic | No |
| ECE regulation number | ECE 106 |
| Section width (mm) | 780 |
| Stat. radius (SLR) [mm] | 756 |
| Rolling circumference [mm]. | 4950 |
| Tread depth (mm) | 25,5 |
| Assembly Item no. Rim | • 32013121 |
| Load capacity of rim 1 [kg] | 11220 |
| Speed Rims 1 [km/h] | 40 |
| Load capacity of rim 2 [kg] | 8250 |
| Speed Rims 2 [km/h] | 65 |
| Maximum speed [km/h]. | 65 |
| Type of drive | Angetriebene & gezogene Achse |
| Number of bolt holes | 10 |
| hub hole diameter [mm]. | 281 |
| Bolt hole circle diameter [mm] | 335 |
| Bolt hole diameter [mm] | 27 |
| Bolt hole design EUWA | B22 ES 36 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R18 |
| Rim centering | BC |
| Rim material | steel |
| RAL | RAL9006 |
| Valve seat | External Valve |
| Ventilation holes | No |

| | |
|--------------------------|------------------|
| Single / multi-part | einteilig |
| Hump | TH2 |
| Cavity Sealed | No |
| Knurling | without knurling |
| Verschweißung beidseitig | No |
| Assembly Item no. Valve | • 47201038 |
| Preassembled valve | No |
| TPMS-kompatibles Ventil | No |
| Valve hole diameter [mm] | 15.7 |
| Valve design | Metal valve |
| Valve designation ETRTO | V5.01.1 |
| Valve length [mm] | 50.0 |
| Valve angle [°] | gerade |