

WHEELS

Product group	Wheels
Item number	59913867
Valid wheel size	750 / 60 - 30.5
Brand	Alliance
Tread pattern	Flotation 328
Valid rim size	AG 24.00 x 30.5 TH2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-100
Rim colour	Silver
Rim series	Profiline
Load capacity complete wheel [kg]	7620
Speed complete wheel [km/h]	50



Technical Informations

Assembly Item no. Tyres	• 15213575
LI / SI / PR	179 B / 172 D, 16 PR
Load capacity 1 [kg]	7750
Speed 1 [km/h].	50
Load capacity 2 [kg]	6300
Speed 2 [km/h].	65
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	339,63

ECE regulation number	ECE 106
Section width (mm)	750
Stat. radius (SLR) [mm]	720
Rolling circumference [mm].	4790
Tread depth (mm)	25,0
E-Ready	No
Assembly Item no. Rim	• 32013122
Load capacity of rim 1 [kg]	11220
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	8050
Speed Rims 2 [km/h]	70
Maximum speed [km/h].	65
Maximum air pressure [bar].	2,50
Type of drive	Towed axle
Hump	TH2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18

hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade