

## WHEELS

Product group	Wheels
Item number	59913879
Valid wheel size	850 / 50 - 30.5
Brand	BKT
Tread pattern	Flotation 648
Valid rim size	AG 28.00 x 30.5 H2
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	9500
Speed complete wheel [km/h]	40



## Technical Informations

Assembly Item no. Tyres	• 15712950
LI / SI / PR	174 A8 / 186 A8, 16 PR
Load capacity 1 [kg]	6700
Speed 1 [km/h].	40
Load capacity 2 [kg]	9500
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	371,28
ECE regulation number	ECE 106
Section width (mm)	850

Stat. radius (SLR) [mm]	710
Rolling circumference [mm].	4935
Tread depth (mm)	26,0
Number of lugs	40x2
E-Ready	No
Assembly Item no. Rim	• 33060852
Load capacity of rim 1 [kg]	11800
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	8700
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	2,20
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18

---

hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade