

## WHEELS

Product group	Wheels
Item number	59913881
Valid wheel size	850 / 50 R 30.5
Brand	BKT
Tread pattern	Ridemax FL 693 M
Valid rim size	AG 28.00 x 30.5 H2
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	8500
Speed complete wheel [km/h]	65



## Technical Informations

Assembly Item no. Tyres	• 15715260
LI / SI / PR	182 D
Load capacity 1 [kg]	8500
Speed 1 [km/h].	65
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	396,71
ECE regulation number	ECE 106
Section width (mm)	862
Stat. radius (SLR) [mm]	719

Rolling circumference [mm].	4925
Tread depth (mm)	26,0
Tyre capacity 75% [litr.]	1006
E-Ready	No
Assembly Item no. Rim	• 33060852
Load capacity of rim 1 [kg]	11800
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	8700
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	4,00
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281

---

<b>Bolt hole circle diameter [mm]</b>	335
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No
<b>Valve design</b>	Metal valve
<b>Valve designation ETRTO</b>	V5.01.1
<b>Valve length [mm]</b>	50.0
<b>Valve angle [°]</b>	gerade