

WHEELS

Product group	Wheels
Item number	59913930
Valid wheel size	30.5L R 32
Brand	Alliance
Tread pattern	390
Valid rim size	TW 27 B x 32
Rim connection	10/281/335
Bolt hole design	B3
Rim colour	Silver
Load capacity complete wheel [kg]	9490
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15215830
LI / SI / PR	181 B
Load capacity 1 [kg]	8250
Speed 1 [km/h].	50
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	426,29
ECE regulation number	ECE 106
Section width (mm)	790
Stat. radius (SLR) [mm]	805

Rolling circumference [mm].	5431
Tread depth (mm)	30,0
Tyre capacity 75% [litr.]	1073
E-Ready	No
Assembly Item no. Rim	• 32013515
Load capacity of rim 1 [kg]	13300
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	10000
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,00
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281

Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade