

WHEELS

Product group	Wheels
Item number	59913937
Valid wheel size	VF 650 / 60 R 26.5
Brand	Alliance
Tread pattern	Agriflex 389 +
Valid rim size	AG 20.00 x 26.5 H2
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Silver
Rim series	Profiline+
Load capacity complete wheel [kg]	6700
Speed complete wheel [km/h]	65



Technical Informations

Assembly Item no. Tyres	• 15215736
LI / SI / PR	174 D
Load capacity 1 [kg]	6700
Speed 1 [km/h].	65
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	257,91
ECE regulation number	ECE 106
Section width (mm)	665
Stat. radius (SLR) [mm]	622

Rolling circumference [mm].	4390
Tread depth (mm)	26,0
Number of lugs	22x2
Tyre capacity 75% [ltr.]	469.5
E-Ready	No
Assembly Item no. Rim	• 32012874
Load capacity of rim 1 [kg]	10200
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7500
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	2,80
Type of drive	Towed axle
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18

hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade