

## WHEELS

Product group	Wheels
Item number	59913942
Valid wheel size	800 / 60 R 32
Brand	Alliance
Tread pattern	390
Valid rim size	TW 27 B x 32
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	9000
Speed complete wheel [km/h]	65
Nettogewicht [kg] (gültig)	453,84
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15215820
LI / SI / PR	184 D / 181 E
Load capacity 1 [kg]	9000
Speed 1 [km/h].	65
Load capacity 2 [kg]	8250
Speed 2 [km/h].	70
Maximum air pressure [bar].	4,00
TL/TT	TL

Tyre colour	Black
E-Ready	No
Carcass properties	Steel Belted
Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	800
Stat. radius (SLR) [mm]	809.00
Rolling circumference [mm].	5456
Tread depth (mm)	31,0
Assembly Item no. Rim	• 32013513
Load capacity of rim 1 [kg]	13300
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	10000
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Type of drive	Towed axle
Number of bolt holes	10
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Bolt hole design EUWA	B22 DS 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve

---

Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Cavity Sealed	No
Knurling	without knurling
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade