

## WHEELS

Product group	Wheels
Item number	59913948
Valid wheel size	VF 800 / 60 R 32
Brand	Alliance
Tread pattern	Agriflex 389 +
Valid rim size	TW 27 B x 32
Rim connection	10/281/335
Bolt hole design	B3
Rim colour	Silver
Load capacity complete wheel [kg]	12240
Speed complete wheel [km/h]	40



## Technical Informations

Assembly Item no. Tyres	• 15215819
LI / SI / PR	188 D
Load capacity 1 [kg]	10000
Speed 1 [km/h].	65
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	432,21
ECE regulation number	ECE 106
Section width (mm)	800
Stat. radius (SLR) [mm]	778

Rolling circumference [mm].	5465
Tread depth (mm)	26,0
Number of lugs	28x2
Tyre capacity 75% [ltr.]	877.5
E-Ready	No
Assembly Item no. Rim	• 32013515
Load capacity of rim 1 [kg]	13300
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	10000
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	2,80
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18

---

hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade