

WHEELS

Product group	Wheels
Item number	59913952
Valid wheel size	800 / 65 R 32
Brand	Alliance
Tread pattern	360
Valid rim size	TW 27 B x 32
Rim connection	10/281/335
Bolt hole design	B3
Rim colour	Silver
Load capacity complete wheel [kg]	8250
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15226767
LI / SI / PR	181 A8 / 178 B
Load capacity 1 [kg]	8250
Speed 1 [km/h].	40
Load capacity 2 [kg]	7500
Speed 2 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	477,10
ECE regulation number	ECE 106
Section width (mm)	800

Stat. radius (SLR) [mm]	825
Rolling circumference [mm].	5533
Tread depth (mm)	49,0
Tyre capacity 75% [ltr.]	868
E-Ready	No
Assembly Item no. Rim	• 32013515
Load capacity of rim 1 [kg]	13300
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	10000
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,60
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18

hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade