

## WHEELS

Product group	Wheels
Item number	59913953
Valid wheel size	800 / 65 R 32
Brand	Alliance
Tread pattern	360
Valid rim size	TW 27 B x 32
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	8250
Speed complete wheel [km/h]	40



## Technical Informations

Assembly Item no. Tyres	• 15226767
LI / SI / PR	181 A8 / 178 B
Load capacity 1 [kg]	8250
Speed 1 [km/h].	40
Load capacity 2 [kg]	7500
Speed 2 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	477,10
ECE regulation number	ECE 106
Section width (mm)	800

Stat. radius (SLR) [mm]	825
Rolling circumference [mm].	5533
Tread depth (mm)	49,0
Tyre capacity 75% [ltr.]	868
E-Ready	No
Assembly Item no. Rim	• 32013513
Load capacity of rim 1 [kg]	13300
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	10000
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	50
Maximum air pressure [bar].	3,60
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Knurling	without knurling

---

Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade