

WHEELS

Product group	Wheels
Item number	59913964
Valid wheel size	420 / 80 R 46
Brand	BKT
Tread pattern	Agrimax RT 855
Valid rim size	W 13 x 46
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+50
Rim colour	Silver
Load capacity complete wheel [kg]	4375
Speed complete wheel [km/h]	65
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Bohnenkamp
Moving Professionals

BKT
GROWING TOGETHER

Technical Informations

Assembly Item no. Tyres	• 15726458
LI / SI / PR	170 A2 / 159 D
Load capacity 1 [kg]	6000
Speed 1 [km/h].	10
Load capacity 2 [kg]	4375
Speed 2 [km/h].	65
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	341,28

ECE regulation number	ECE 106
Section width (mm)	418
Stat. radius (SLR) [mm]	863
Rolling circumference [mm].	5641
Tread depth (mm)	51,0
Number of lugs	26x2
Tyre capacity 75% [ltr.]	371.75
E-Ready	No
Assembly Item no. Rim	• 39123115
Load capacity of rim 1 [kg]	6500
Speed Rims 1 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	3,20
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade