

WHEELS

Product group	Wheels
Item number	59913966
Valid wheel size	420 / 80 R 46
Brand	Alliance
Tread pattern	385
Valid rim size	W 13 x 46
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+100
Rim colour	Silver
Load capacity complete wheel [kg]	4670
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15227412
LI / SI / PR	162 A8 / 159 D
Load capacity 1 [kg]	4750
Speed 1 [km/h].	40
Load capacity 2 [kg]	4375
Speed 2 [km/h].	65
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	323,03
ECE regulation number	ECE 106

Section width (mm)	420
Stat. radius (SLR) [mm]	859
Rolling circumference [mm].	5611
Tyre capacity 75% [ltr.]	321
E-Ready	No
Assembly Item no. Rim	• 39122986
Load capacity of rim 1 [kg]	4670
Speed Rims 1 [km/h]	50
Maximum speed [km/h].	50
Maximum air pressure [bar].	3,20
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
Surface treatment	SB
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	15
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281

Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade