

WHEELS

Product group	Wheels
Item number	59913967
Valid wheel size	420 / 80 R 46
Brand	Alliance
Tread pattern	Agri Star II
Valid rim size	W 13 x 46
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+50
Rim colour	Silver
Load capacity complete wheel [kg]	4375
Speed complete wheel [km/h]	65
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 10000151
LI / SI / PR	159 D
Load capacity 1 [kg]	4375
Speed 1 [km/h].	65
TRA Code	R1
Carcass properties	Stubble Guard
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	330,41

ECE regulation number	ECE 106
Section width (mm)	418
Stat. radius (SLR) [mm]	860
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5598
Tread depth (mm)	51,0
Number of lugs	26x2
Tyre capacity 75% [ltr.]	297.52
E-Ready	No
Assembly Item no. Rim	• 39123115
Load capacity of rim 1 [kg]	6500
Speed Rims 1 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	3,60
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006

Cavity Sealed	No
Disc thickness [mm]	15
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade