

## WHEELS

Product group	Wheels
Item number	59913973
Valid wheel size	520 / 85 R 46
Brand	Alliance
Tread pattern	Agristar 375
Valid rim size	DW 16 L x 46
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+70
Rim colour	Red
Load capacity complete wheel [kg]	6500
Speed complete wheel [km/h]	40



## Technical Informations

Assembly Item no. Tyres	• 15227430
LI / SI / PR	173 A8 / 169 D
Load capacity 1 [kg]	6500
Speed 1 [km/h].	40
Load capacity 2 [kg]	5800
Speed 2 [km/h].	65
Direction	Left
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	417,73
ECE regulation number	ECE 106

Section width (mm)	542
Stat. radius (SLR) [mm]	956
Speed Radius Index (SRI)	1025
Rolling circumference [mm].	6284
Tread depth (mm)	60,0
Number of lugs	23x2
Tyre capacity 75% [ltr.]	580
E-Ready	No
Assembly Item no. Rim	• 39122982
Load capacity of rim 1 [kg]	7475
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	4200
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	3,20
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
Surface treatment	SB
RAL	RAL3000
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36

---

<b>Bolt hole diameter [mm]</b>	27
<b>Countersinking</b>	Sphere
<b>Spherical countersink [mm].</b>	R18
<b>hub hole diameter [mm].</b>	281
<b>Bolt hole circle diameter [mm]</b>	335
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No
<b>Valve design</b>	Metal valve
<b>Valve designation ETRTO</b>	V5.01.1
<b>Valve length [mm]</b>	50.0
<b>Valve angle [°]</b>	gerade