

WHEELS

Product group	Wheels
Item number	59913976
Valid wheel size	520 / 85 R 46
Brand	BKT
Tread pattern	Agrimax RT 855
Valid rim size	DW 16 L x 46
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-125
Rim colour	Silver
Load capacity complete wheel [kg]	5320
Speed complete wheel [km/h]	50
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Bohnenkamp
■ ■ ● Moving Professionals

BKT
GROWING TOGETHER

Technical Informations

Assembly Item no. Tyres	• 15726472
LI / SI / PR	173 A8 / 173 B
Load capacity 1 [kg]	6500
Speed 1 [km/h].	40
Load capacity 2 [kg]	6500
Speed 2 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	431,75

ECE regulation number	ECE 106
Section width (mm)	516
Stat. radius (SLR) [mm]	964
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6310
Tread depth (mm)	56,5
Number of lugs	24x2
Tyre capacity 75% [ltr.]	594
E-Ready	No
Assembly Item no. Rim	• 39123161
Load capacity of rim 1 [kg]	5320
Speed Rims 1 [km/h]	65
Maximum speed [km/h].	50
Maximum air pressure [bar].	4,00
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel

RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade