

WHEELS

Product group	Wheels
Item number	59913990
Valid wheel size	800 / 45 - 26.5
Brand	Alliance
Tread pattern	Flotation 328
Valid rim size	AG 28.00 x 26.5 TH2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-50
Rim colour	Silver
Rim series	Profiline
Load capacity complete wheel [kg]	7300
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15212870
LI / SI / PR	164 A8 / 177 A8, 16 PR
Load capacity 1 [kg]	5000
Speed 1 [km/h].	40
Load capacity 2 [kg]	7300
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	277,06
ECE regulation number	ECE 106

Section width (mm)	800
Stat. radius (SLR) [mm]	614
Speed Radius Index (SRI)	650
Rolling circumference [mm].	4050
Tread depth (mm)	25,0
E-Ready	No
Assembly Item no. Rim	• 32013031
Load capacity of rim 1 [kg]	9930
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7300
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	50
Maximum air pressure [bar].	2,20
Type of drive	Angetriebene & gezogene Achse
Hump	TH2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere

Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade