

WHEELS

Product group	Wheels
Item number	59914209
Valid wheel size	28L - 26
Brand	Alliance
Tread pattern	330
Valid rim size	DW 25 B x 26
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	-100
Rim colour	Silver
Load capacity complete wheel [kg]	6500
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15222391
LI / SI / PR	173 A8, 16 PR
Load capacity 1 [kg]	6500
Speed 1 [km/h].	40
Carcass properties	HD
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	277,01
ECE regulation number	ECE 106
Section width (mm)	714
Stat. radius (SLR) [mm]	702

Rolling circumference [mm].	4627
Tread depth (mm)	28,0
E-Ready	No
Assembly Item no. Rim	• 32010445
Load capacity of rim 1 [kg]	9660
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7100
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	2,20
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Number of additional holes	6
Additional pitch circle diameter [mm].	430
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281

Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade