

## WHEELS

Product group	Wheels
Item number	59914210
Valid wheel size	28L - 26
Brand	Alliance
Tread pattern	330
Valid rim size	DW 25 B x 26
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	6500
Speed complete wheel [km/h]	40



## Technical Informations

Assembly Item no. Tyres	• 15222391
LI / SI / PR	173 A8, 16 PR
Load capacity 1 [kg]	6500
Speed 1 [km/h].	40
Carcass properties	HD
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	284,15
ECE regulation number	ECE 106
Section width (mm)	714
Stat. radius (SLR) [mm]	702

Rolling circumference [mm].	4627
Tread depth (mm)	28,0
E-Ready	No
Assembly Item no. Rim	• 32010433
Load capacity of rim 1 [kg]	9660
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7300
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	2,20
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335

---

Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade