

## WHEELS

Product group	Wheels
Item number	59914302
Valid wheel size	23.1 - 26
Brand	BKT
Tread pattern	TR 387
Valid rim size	DW 20 B x 26
Rim connection	10/281/335
Bolt hole design	B3
Rim colour	Silver
Load capacity complete wheel [kg]	5000
Speed complete wheel [km/h]	30



## Technical Informations

Assembly Item no. Tyres	• 15772440
LI / SI / PR	164 A6, 12 PR
Load capacity 1 [kg]	5000
Speed 1 [km/h].	30
Carcass properties	HD
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	230,07
ECE regulation number	ECE 106
Section width (mm)	592
Stat. radius (SLR) [mm]	690

Rolling circumference [mm].	4688
Tread depth (mm)	27,0
E-Ready	No
Assembly Item no. Rim	• 32010402
Load capacity of rim 1 [kg]	6000
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	5400
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	30
Maximum air pressure [bar].	1,70
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve

---

Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade