

WHEELS

Product group	Wheels
Item number	59914351
Valid wheel size	30.5L R 32
Brand	BKT
Tread pattern	Ridemax FL 690
Valid rim size	TW 27 B x 32
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	8250
Speed complete wheel [km/h]	50



Technical Informations

Assembly Item no. Tyres	• 15715280
LI / SI / PR	181 B
Load capacity 1 [kg]	8250
Speed 1 [km/h].	50
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	455,04
ECE regulation number	ECE 106
Section width (mm)	790
Stat. radius (SLR) [mm]	806

Rolling circumference [mm].	5430
Tread depth (mm)	31,0
E-Ready	No
Assembly Item no. Rim	• 32013513
Load capacity of rim 1 [kg]	13300
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	10000
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	50
Maximum air pressure [bar].	3,00
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335

Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade