

WHEELS

Product group	Wheels
Item number	59914357
Valid wheel size	800 / 60 R 32
Brand	BKT
Tread pattern	Ridemax FL 690
Valid rim size	TW 27 B x 32
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+30
Rim colour	Black
Load capacity complete wheel [kg]	9000
Speed complete wheel [km/h]	65
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15715269
LI / SI / PR	185 D
Load capacity 1 [kg]	9250
Speed 1 [km/h].	65
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	467,94
ECE regulation number	ECE 106

Section width (mm)	800
Stat. radius (SLR) [mm]	817
Rolling circumference [mm].	5454
Tread depth (mm)	31,0
E-Ready	No
Assembly Item no. Rim	• 32013516
Load capacity of rim 1 [kg]	12240
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	9000
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	4,00
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9005
Colour type	Glossy
Cavity Sealed	No

Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade