

WHEELS

Product group	Wheels
Item number	59914425
Valid wheel size	650 / 55 R 26.5
Brand	Nokian
Tread pattern	CT
Valid rim size	AG 20.00 x 26.5 H2
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Silver
Rim series	Profiline+HD
Load capacity complete wheel [kg]	7300
Speed complete wheel [km/h]	65



Technical Informations

Assembly Item no. Tyres	• 17415700
LI / SI / PR	177 D
Load capacity 1 [kg]	7300
Speed 1 [km/h].	65
Carcass properties	HD Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	311,49
ECE regulation number	not necessary
Section width (mm)	645
Stat. radius (SLR) [mm]	639

Rolling circumference [mm].	4247
Tread depth (mm)	27,0
E-Ready	No
Assembly Item no. Rim	• 32013802
Load capacity of rim 1 [kg]	13500
Speed Rims 1 [km/h]	10
Load capacity of rim 2 [kg]	7500
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	6,00
Type of drive	Towed axle
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335

Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade