

WHEELS

Product group	Wheels
Item number	59914426
Valid wheel size	650 / 55 R 26.5
Brand	Nokian
Tread pattern	CT
Valid rim size	AG 20.00 x 26.5 H2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-50
Rim colour	Silver
Rim series	Profiline+HD
Load capacity complete wheel [kg]	7300
Speed complete wheel [km/h]	65
Nettogewicht [kg] (gültig)	308,59
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



nokian®
TYRES

Technical Informations

Assembly Item no. Tyres	• 17415700
LI / SI / PR	177 D
Load capacity 1 [kg]	7300
Speed 1 [km/h].	65
Maximum air pressure [bar].	6,00
TL/TT	TL
Tyre colour	Black

E-Ready	No
Carcass properties	HD Steel Belted
Antistatic	No
ECE regulation number	not necessary
Section width (mm)	645
Stat. radius (SLR) [mm]	639
Rolling circumference [mm].	4247
Tread depth (mm)	27,0
Assembly Item no. Rim	• 32013803
Load capacity of rim 1 [kg]	13500
Speed Rims 1 [km/h]	10
Load capacity of rim 2 [kg]	7500
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Type of drive	Towed axle
Number of bolt holes	10
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Bolt hole design EUWA	B22 ES 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No

Single / multi-part	einteilig
Hump	H2
Valve protection	VSH
Cavity Sealed	No
Knurling	without knurling
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade