

## WHEELS

Product group	Wheels
Item number	59914428
Valid wheel size	600 / 60 R 30.5
Brand	Nokian
Tread pattern	CT
Valid rim size	AG 20.00 x 30.5 H2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-50
Rim colour	Silver
Rim series	Profiline+
Load capacity complete wheel [kg]	6500
Speed complete wheel [km/h]	65



## Technical Informations

Assembly Item no. Tyres	• 17415920
LI / SI / PR	173 D
Load capacity 1 [kg]	6500
Speed 1 [km/h].	65
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	329,40
ECE regulation number	not necessary
Section width (mm)	610
Stat. radius (SLR) [mm]	681

Rolling circumference [mm].	4570
Tread depth (mm)	26,0
Tyre capacity 75% [ltr.]	420
E-Ready	No
Assembly Item no. Rim	• 32013099
Load capacity of rim 1 [kg]	9660
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7100
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	5,00
Type of drive	Towed axle
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281

---

<b>Bolt hole circle diameter [mm]</b>	335
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No
<b>Valve design</b>	Metal valve
<b>Valve designation ETRTO</b>	V5.01.1
<b>Valve length [mm]</b>	50.0
<b>Valve angle [°]</b>	gerade