

## WHEELS

Product group	Wheels
Item number	59914453
Valid wheel size	560 / 60 R 22.5
Brand	Nokian
Tread pattern	CT
Valid rim size	AG 16.00 x 22.5 H2
Rim connection	8/221/275
Bolt hole design	A2
Offset (mm)	-50
Rim colour	Silver
Rim series	Profiline+
Load capacity complete wheel [kg]	5150
Speed complete wheel [km/h]	65
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 17415850
LI / SI / PR	165 D
Load capacity 1 [kg]	5150
Speed 1 [km/h].	65
Carcass properties	HD Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	189,22

ECE regulation number	not necessary
Section width (mm)	560
Stat. radius (SLR) [mm]	555
Rolling circumference [mm].	3811
Tread depth (mm)	22,0
Tyre capacity 75% [ltr.]	295
E-Ready	No
Assembly Item no. Rim	• 31612676
Load capacity of rim 1 [kg]	7010
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5150
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	5,00
Number of bolt holes	8
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006

---

Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade