

WHEELS

Product group	Wheels
Item number	59914650
Valid wheel size	20.5 R 25
Brand	BKT
Tread pattern	Earthmax SR 30
Valid rim size	17.00 - 25
Rim connection	12/371/425
Bolt hole design	A3
Offset (mm)	+27
Rim colour	Silver
Load capacity complete wheel [kg]	5330
Speed complete wheel [km/h]	12



Technical Informations

Assembly Item no. Tyres	• 15785450
LI / SI / PR	186 A2 / 177 B
Load capacity 1 [kg]	9500
Speed 1 [km/h].	10
Load capacity 2 [kg]	7300
Speed 2 [km/h].	50
TRA Code	E3 L3
Star Rating	** *
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black

Nettogewicht [kg] (gültig)	351,06
ECE regulation number	not necessary
Section width (mm)	529
Stat. radius (SLR) [mm]	663
Rolling circumference [mm].	4439
Tread depth (mm)	32,0
Tyre capacity 75% [ltr.]	345
E-Ready	No
Assembly Item no. Rim	• 32013620
Load capacity of rim 1 [kg]	5330
Speed Rims 1 [km/h]	12
Maximum speed [km/h].	12
Maximum air pressure [bar].	5,25
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	mehrteilig
Quantity multi-piece	three-part
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	12
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27

Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	371
Bolt hole circle diameter [mm]	425
Valve seat	External Valve
Valve hole diameter [mm]	20.5
Preassembled valve	No
Valve designation ETRTO	V5.10.1
Valve length [mm]	17
Valve angle [°]	gerade