

WHEELS

Product group	Wheels
Item number	59914970
Valid wheel size	220 / 55 R 12
Brand	Alliance
Tread pattern	579
Valid rim size	7 I x 12 H2
Rim connection	5/80/114.3
Offset (mm)	-10.5
Rim colour	Silver
Load capacity complete wheel [kg]	475
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15226930
LI / SI / PR	82 A8 / 82 B
Load capacity 1 [kg]	475
Speed 1 [km/h].	40
Load capacity 2 [kg]	475
Speed 2 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	17,31
ECE regulation number	ECE 106
Section width (mm)	220

Stat. radius (SLR) [mm]	252
Rolling circumference [mm].	1639
Tread depth (mm)	13,0
E-Ready	No
Assembly Item no. Rim	• 39600418
Load capacity of rim 1 [kg]	900
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	2,40
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	13
hub hole diameter [mm].	80
Bolt hole circle diameter [mm]	114.3
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1

Valve length [mm]	43.0
Valve angle [°]	gerade
