Bohnenkamp Moving Professionals

20.09.2024

WHEELS

Product group	Wheels
Item number	59914971
Valid wheel size	280 / 70 R 18
Brand	Alliance
Tread pattern	579
Valid rim size	W 9 x 18 H2
Rim connection	5/108/139.5
Offset (mm)	-13
Rim colour	Silver
Load capacity complete wheel [kg]	750
Speed complete wheel [km/h]	30





Technical Informations

Assembly Item no. Tyres	15226963
LI / SI / PR	114 A8 / 114 B
Load capacity 1 [kg]	1180
Speed 1 [km/h].	40
Load capacity 2 [kg]	1180
Speed 2 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	53,46
ECE regulation number	ECE 106
Section width (mm)	282

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

20.09.2024

Stat. radius (SLR) [mm]	387
Rolling circumference [mm].	2530
Tread depth (mm)	24,0
E-Ready	No
Assembly Item no. Rim •	39600419
Load capacity of rim 1 [kg]	750
Speed Rims 1 [km/h]	30
Maximum speed [km/h].	30
Maximum air pressure [bar].	2,40
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	17.5
hub hole diameter [mm].	108
Bolt hole circle diameter [mm]	139.5
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.3

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Valve length [mm]	43.0
Valve angle [°]	gerade

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.