

WHEELS

Product group	Wheels
Item number	59915002
Valid wheel size	385 / 65 R 22.5
Brand	Alliance
Tread pattern	882
Valid rim size	11.75 x 22.5
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	-100
Rim colour	Red
Load capacity complete wheel [kg]	5000
Speed complete wheel [km/h]	65



Technical Informations

Assembly Item no. Tyres	• 15215520
LI / SI / PR	164 D
Load capacity 1 [kg]	5000
Speed 1 [km/h].	65
Carcass properties	Steel Belted
Direction	Right
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	132,73
ECE regulation number	ECE 106
Section width (mm)	389

Stat. radius (SLR) [mm]	493
Rolling circumference [mm].	3205
Tread depth (mm)	12,7
E-Ready	No
Assembly Item no. Rim	• 33060277
Load capacity of rim 1 [kg]	5000
Speed Rims 1 [km/h]	65
Load capacity of rim 2 [kg]	4800
Speed Rims 2 [km/h]	80
Maximum speed [km/h].	65
Maximum air pressure [bar].	9,00
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL3000
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335

Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade